







APPLICATION

LED lighting

LED WATERPROOF DRIVER 24V | 30W

TECHNICAL DATA

SKU : 6002 MODEL : TRW24-30W

WATTS: 30W BODY TYPE: Aluminum Alloy

DIMENSION: 125x38x21mm UNIT COLOR: Steel Blue

INPUT VOLTAGE : 110V-255V, 50/60Hz

INPUT CURRENT : 1.2A 1.1A

OUTPUT VOLTAGE: 24V

OUTPUT CURRENT: 1.5A

EFFICIANCY : 0.88 WEIGHT :

PROTECTION

SHORT CIRCUT

The power supply can resume normal operation when the short circuit is removed during power supply.

Terrioved during power supply

OVERLOAD Protection type:Hiccup mode,recovers automatically after fault condition is

OVER CURRENT

After the over current fault is removed, the power supply will automatically resume normal operation

resume normal operation

When the output voltage exceeds the rated voltage, the power supply will be

OVER VOLTAGE

when the output voltage exceeds the rated voltage, the power supply will be protected and normal operation can be resumed after the fault is removed.

ENVIRONMENT

WORKING TEMPERATURE: -20°C +45°C 20%~90%RH

WORKING HUMIDITY : 40°C +85°C 10%~95%RH

STORAGE TEMP. : 20°C~+85°C 10%~95%RH

TEMP. COEFFCIEN : $\pm 0.03\%$ °C (0-5°C)

VIBRATION : 10-500Hz, 2G 10min. / 1 cycle, 60 min.

each axes